

# Material Safety Data Sheet

# Tribolube-37RPA

May be used to comply with OSHA's Hazard Communication Standard.  
29 CFR 1910.1200 Standard must be consulted for specific requirements.

QUICK IDENTIFIER  
Common Name: (used on Label and list)

## SECTION 1- MANUFACTURER

Manufacturer's  
Name

*Aerospace Lubricants, Inc*

Address

*1600 Georgesville Road*

Emergency  
Telephone No.

*614-878-3600*

City, State, and Zip

*Columbus, Ohio 43228*

Other  
Information  
Calls

*614-878-3600*

Signature of Person



Date *January 3, 2006*

Responsible for Preparation

*Stephen E. Gates*

Prepared

*Rev. D*

HEALTH

1

FLAMMABILITY

0

REACTIVITY

0

PERSONAL PROTECTION

B

## SECTION 2- HAZARDOUS INGREDIENTS/IDENTITY

Hazardous Component(s) (chemical & common name(s))	OSHA PEL	ACGIH TLV	Other Exposure Limits	% (optional)	CAS NO.
--	-------------	--------------	--------------------------	-----------------	------------

No hazardous components were knowingly incorporated into this lubricant. This product is not considered hazardous according to the OSHA

Hazardous Communication Standard 29CFR 1910.1200

Threshold Limit Value: LD50>40G/KG (Non-toxic)

OSHA Threshold Limit Value: LD50>40G/KG

ACGIH Threshold Limit Value: LD50>40G/KG

Carcinogen - NTP Program: N/A

Carcinogen - IARC Program: N/A

## SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point	N/A	Specific Gravity (H O=1)	1.90	Vapor Pressure (mm Hg)	10 <sup>-6</sup> at 20°C
Solubility in Water	Insoluble	Reactivity in Water	Non-reactive		
Appearance and Odor	White, Odorless	Melting Point	Above 250°C		
		Vapor Density (Air=1)	N/A		

## SECTION 4 - FIRE & EXPLOSION DATA

Flash Point	N/A	Method Used	N/A	Flammable Limits in Air % by Volume	N/A	LEL Lower	N/A	UEL Upper	N/A
Auto-Ignition Temperature	Nonflammable	Extinguisher Media	N/A						

Special Fire

Fighting Procedures

Self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. Decomposition

at temperatures above 290°C may cause the evolution of toxic gaseous fluorine compounds.

Unusual Fire and  
Explosion Hazards

Toxic fluorine gases are by-products of combustion.

## SECTION 5 - PHYSICAL HAZARDS (REACTIVITY DATA)

**Tribolube-37RPA**

Stability Unstable  Conditions to Avoid  Stable  Avoid heating above 250°C.

Incompatibility (Materials to Avoid) Molten alkali metals, interhalogen compounds, strong or nonaqueous alkali and Lewis acids above 100°C

Hazardous Decomposition Products Toxic Fluorine gases

Hazardous polymerization May Occur  Will Not Occur  Conditions to Avoid Avoid heating above 250°C

## SECTION 6 - HEALTH HAZARDS

1. Acute None 2. Chronic None

Signs and Symptom of Exposure Mild irritant to the skin upon prolonged exposure for some individuals.

Decomposition products formed at high temperatures above 250°C may cause "polymer fever."

Medical Condition Generally Aggravated by Exposure No known medical condition that might be aggravated by exposure.

Chemical Listed as Carcinogen or Potential Carcinogen None National Toxicology Program Yes  No  I.A.R.C. Monographs Yes  No  OSHA Yes  No

Emergency and First Aid Procedures See below

### ROUTES OF ENTRY

- Inhalation Slightly toxic by inhalation (4 hr. LC 50 1,000-5000 ppm; 8-40 mg/l). If discomfort occurs, move to fresh air; contact physician.
- Eyes Flush with water; if irritated, contact physician.
- Skin Wipe off and wash with soap and water. If irritation develops, contact physician.
- Ingestion Very low toxicity by contact (LD50 > 10,000 mg/kg). Very low toxicity by ingestion (oral LD50 > 5,000 mg/kg). Give large amounts of water; contact physician. Inform physician product is inert/non-toxic.

## SECTION 7 - SPECIAL PRECAUTION AND SPILL/LEAK PROCEDURES

Precautions to be Taken in Handling and Storage Use reasonable care. Do not store above 250°F or near flammables or explosive material.

Other Precautions Toxic vapors may evolve above 250°C; provide adequate ventilation if used above this temperature.

Avoid spills: causes slippery surfaces.

Steps to be Taken in Case Material is Released or Spilled Scrape up with proper tools; wipe up with absorbant cloth or paper towel; apply non-skid absorbant material to floor. Collect waste materials for salvage or disposal.

Waste Disposal Methods (Consult federal, state, and local regulations) Dispose of in accordance with current Federal, State, and Local Regulations.

## SECTION 8 - SPECIAL PROTECTION INFORMATION/CONTROL MEASURES

Respiratory Protection (Specify Type) Not required unless product is being used as a mist.

Ventilation	Local Exhaust	Mechanical (General)	Special	Other
Recommended	Not required	Recommended	Not required	

Protective Gloves Plastic disposable Eye Protection Safety glasses recommended

Other Protective Clothing or Equipment Plastic apron, fabric laboratory coat recommended.

Work/Hygienic Practices Do not contaminate smoking materials; wash hands and / or contaminated area after exposure.