

TRIBOLUBE[®]-021306

Special Purpose Grease

CHARACTERISTICS

Tribolube-021306 has a temperature range of -54°C to 149°C, is a silica thickened, light viscosity Silicone grease.

APPLICATIONS

This grease is intended for use in cable applications where either rotation or push-pull and low forces are required.

PERFORMANCE TEST	TEST METHOD	CONDITION	TYPICAL VALUES
Temperature Range			-54°C to 149°C
Unworked Penetration	ASTM D-1403	@ 77°F	281
Worked Penetration	ASTM D-1403	60 Strokes @ 77°F	333
Dropping Point	ASTM D-2265		<308°C
Copper Corrosion	ASTM D-4048	24 hrs @ 100°C	1B, shiny
Evaporation	ASTM D-2595	22 hrs @ 100°C	0.43%
Oil Separation	FED-STD-791 Method 321	30 hrs @ 100°C	1.88%
Water Washout	ASTM D-1264	@ 38°C	7.09%
Low Temperature Torque	ASTM D-1478	-40°C, Starting	390 gm-cm
		Running	91 gm-cm

Information represented here should not be used for preparing specifications. Please consult a lubrication engineer at Aerospace Lubricants, Inc. to help prepare a specification. This information relates only to the specific material contained herein and may not be valid for such material used in combination with any other materials or in any process, and is not to be considered a warranty or quality specification.