



TriboFrack P55-000

Aluminum Complex Fracking Grease

CHARACTERISTICS

- Easily pumpable
- Highly compatible
- Exceptional mechanical stability
- Excellent protection from corrosion

APPLICATIONS

TriboFrack P55-000 was developed for harsh and demanding environments. This product has been designed to allow our product to pump easily while staying in place. TriboFrack P55-000 is compatible with typical rod and packing materials such as Brass, Teflon, Kevlar, Rubber, Graphite, etc. making it an ideal plunger and packing lubricant for fracking systems.

PERFORMANCE DESCRIPTION	TEST METHOD	CONDITION	TYPICAL VALUES
Appearance/Color		Visual	Red
Base Oil			Mineral
Base Oil Viscosity	ASTM D-445	40°C	55 cSt
Base Oil Viscosity w/polymer	ASTM D-445	40°C	220 cSt
Thickener			Aluminum Complex
Dropping point (Base)	ASTM D-2265	°C	> 204
NLGI Grade			000
Worked penetration (x60)	ASTM D-217	25°C (77°F)	410 - 485
Extreme Pressure Properties (4 Ball Method)	ASTM D-2596	Weld Load, min	315 kgf
Specific Gravity	ASTM D-891	25°C (77°F)	0.90
Water Solubility			None

Disclaimer: Values given represent typical properties only and are not intended for use in preparing specifications. Please consult with an ALI applications engineer before writing specifications.

FOR A WORLD IN MOTION

Aerospace Lubricants, Inc.
 1600 Georgesville Rd w Columbus, Ohio 43228 w 614.878.3600 w 800.441.9160 w Fax 614.878.1600
 aerospacelubricants.com w info@aerospacelubricants.com