

Alisyn[®] ProDrive 21 Type 1

Synthetic Lubricating Oil

CHARACTERISTICS

Alisyn Prodrive 21 Type 1 offers the performance advantage of super low viscosity with the protection of a heavy-duty motor oil. In addition, it is an oxidatively stable, corrosion resistant, wide temperature range synthetic lubricating oil. It is compatible with most plastic, elastomeric, and rubber seals, gaskets, and O-rings, except EPDM rubber.

APPLICATIONS

Alisyn ProDrive 21 Type 1 is race proven in the most demanding racing environments... from Indy Cars, GTP Lights,

SCCA Endurance Cars, Pro Stock, and Pro Modified drag cars, to high performance marine engines. The additive package was formulated to give exceptional load carrying capabilities (+4500 lb. Falex loads) while offering superior oxidation stability compared to other lubricants on the market. Customers report reduced operating temperatures up to 45°F when compared to conventional lubricants and up to 30°F compared to other synthetic motor oils. These performance characteristics result in operating efficiency increases of up to 15%.

| PERFORMANCE TEST | TEST METHOD | CONDITION | TYPICAL VALUES |
|----------------------------|-------------|--|--------------------|
| Temperature Range | | | -80°F to 300°F |
| SAE No. | | | < 0W |
| ISO VG | ASTM D-2422 | | 15 |
| Viscosity | ASTM D-445 | @ 210°F | 36.7 SUS/3.16 cSt |
| | | @ 100°F | 74.3 SUS/14.20 cSt |
| | | @ 0°F | 247 cSt |
| | | @ -40°F | 2,560 cSt |
| | | @ -65°F | 18,900 cSt |
| Viscosity Index | ASTM D-2270 | | 85 |
| Evaporation | ASTM D-2595 | 6.5 hrs @ 400°F | 2.0% |
| Flash Point | ASTM D-92 | | 360°F |
| Fire Point | ASTM D-92 | | 390°F |
| Pour Point | ASTM D-97 | | -80°F |
| Load Wear Index | ASTM D-2783 | | 36.30 |
| Last Non-Seizure | | Load/Wear Scar | 80 kg/0.41 mm |
| Last Seizure | | Load/Wear Scar | 160 kg/2.19 mm |
| Weld Load | | Load | 200 kg |
| Steel-on-Steel Wear | ASTM D-4172 | 1200 rpm, 40 kg, 52100 Steel, 1 hr | 0.65 mm |
| Specific Gravity | ASTM D1298 | @ 60°/60°F | 0.8368 |
| API Gravity | ASTM D-1298 | | 37.6 |
| Rust Preventive Properties | ASTM D-665 | Procedure A | Pass |
| | | Procedure B | Pass |
| Oxidation Test | ASTM D-2893 | 312 hrs @ 203°F | |
| | | Viscosity Incr. @ 212°F | 0.97% |
| | | Precipitation No., Orig. | 0.0 |
| | | Precipitation No., Orig. | 0.03 ml |
| Foam Test | ASTM D-892 | Sequence 1 (mls @ 5 min air/mls settling) | 15/0 @ 5 sec |
| | | Sequence 2 (mls @ 5 min air/mls settling) | 15/0 @ 3 sec |
| | | Sequence 3 (mls @ 5 min air/mls settling) | 20/0 @ 5 sec |
| Falex EP Test | ASTM D-3233 | Last Pass Load | 4,500 lbs |
| | | Conv. to Contact Pressure | 210,000 psi |
| Timken Load Arm | ASTM D-2782 | OK Load, lbs | +90 |
| | | Fail Load, lbs | +90 |
| FZG Gear Test | | Load Stage | + 12 Stage |